

2082-ADJUSTABLE CRANE JIB



The 2082 has been designed to convert a standard forklift truck into a universal mobile crane unit (as the 2081). With the benefit of having an adjustable lifting angle for the movement of tall and awkward items such as roof trusses.

Product Code	Capacity (kg)	Extension Range (mm)	Fork pocket (mm)	Height (mm)	Width (mm)	Weight (kg)
2082	2500	700-3700	190x80	635	640*	210
2082	5000	700-3700	190x80	635	640*	210

* Including restraint pin

LOAD RATING FOR 2500Kg MODEL

Length (mm)	610	810	1010	1210	1410	1610	2100	2300	2500	2700	2900	3100	3300	3500	3700
Load (Kg)	2500	2500	2500	2500	1800	1400	1200	1050	950	850	770	700	650	600	560

LOAD RATING FOR 5000Kg MODEL

Length (mm)	610	810	1010	1210	1410	1610	2100	2300	2500	2700	2900	3100	3300	3500	3700
Load (Kg)	5000	3550	2750	2500	2250	1950	1700	1600	1500	1450	1250	1100	1050	1000	950

This unit must be used in conjunction with your machines capabilities, please refer to the machine manufacturers guidelines for further information.

Appearance may vary from picture above.

Eichinger Equipment Ltd
 69-73 James Road, Frimley, Camberley, GU15 2RH
 T: 01276 605 970 F: 01276 682 913 E: sales@eichinger.co.uk